







CLEANER

MP

Multi-Purpose Law Pressure Polyurethane Foam Sealant Cleaner READ CAUTIONS ON REAR PANEL. NET WT. 12oz (436mi) (348

Disponsers

CLEANER

Titebond® WeatherMaster™ X-TREME Multi-Purpose Cleaner is designed to clean up WeatherMaster X-TREME foam sealants. This product is an acetone cleaner and is not meant to be used on surfaces that are not solvent or acetone resistant. The Cleaner is a spray solvent used to dissolve uncured foam. X-TREME Cleaner can also be attached to the WeatherMaster X-TREME Dispensing Unit, allowing it to be flushed and kept clean and operable.

- CLEANS FOAM DISPENSING UNIT
- REMOVES ADHESIVES AND UNCURED FOAM
- GENERAL PURPOSE CLEANER

PHYSICAL AND CHEMICAL CHARACTERISTICS:

Type: Polyurethane foam sealant remover

Flashpoint: 0° F (-18° C)

Freeze/Thaw Stability: Stable

Shelf Life: 5 years

Reactive VOC: 0 g/L

LIMITED WARRANTY: Buyer assumes all risks of use, handling and storage of product not in strict accordance with label directions. Liability for any incidental or consequential damage or loss is specifically excluded at all times. Any implied warranty of merchantability or fitness for particular use is excluded. Seller will not accept liability for more than product replacement.

APPLICATION INSTRUCTIONS

Dispensing Unit cleaning option: While holding the spray activator aside, screw the X-TREME Multi-Purpose Cleaner container into the basket adaptor until it will go no further. Do not overtighten. Carefully pull the Dispensing Unit trigger until solvent extrudes from the gun. Release the Dispensing Unit trigger and let the solvent soak in the Dispensing Unit for one to two minutes. Pull Dispensing Unit trigger and dispense solvent into a suitable container. If necessary, repeat process until only clear solvent appears. Do not store Dispensing Unit with X-TREME Multi-Purpose Cleaner attached. For best results store Dispensing Unit with a fresh can of X-TREME foam sealant or adhesive.

LIMITATIONS

- Flush Dispensing Unit after every 10 to 20 cans of foam or adhesive
- Wear protective glasses or goggles, nitrile gloves and clothing that protects against dermal exposure.
- Use only in a well ventilated area.
- Do not use in horizontal position.

For questions, please call our Help Line at 1.800.347.4583 or visit us at Titebond.com.

CAUTION STATEMENT

DANGER: Extremely flammable aerosol. Contains gas under pressure and may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist, vapors, or spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, and eye protection. FIRST AID: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove any contact lenses and continue rinsing. If irritation persists: Get medical advice or attention. FIRE: In case of fire: Use water fog, foam, dry chemical, or CO₂ for extinction. Eliminate all ignition sources if safe to do so. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Dispose of contents and container in accordance with applicable local, regional, national, or international regulations. For additional information, refer to Safety Data Sheet.



Produc	:t # Size	Weight	UPC	Case UPC	Units Per Package	Packages Per Pallet	
855	l 12 oz.	14 lbs./Case	037083085518	10037083085515	12	75	

Franklin International

Sales: 1.800.669.4583 / Technical: 1.800.347.4583 ©2016 BCM 4/16 FF1038





. ŚŚ 🕻 📢